



Performance level

- | ACEA: C2 / C3
- | API SN
- | BMW: LL04
- | MB: 229.51
- | PORSCHE : C30
- | VW: 504.00/507.00
- | FIAT 9.55535-S1
- | GM DEXOS 2

SYNTH-ULTRA 5W30

This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.



Applications

This fuel economy motor oil can be used in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans where extended oil drain intervals are possible. This oil meets the requirements of the VW 504.00/507.00 standard, in practice also called VW Longlife III.

Characteristics

	Unit	Average Value
Density at 15°C	kg/l	0.848
Viscosity 40°C	mm ² /s	74.3
Viscosity 100°C	mm ² /s	12.4
Viscosity -30°C	mPas	6060
Viscosity index		166
Flash point COC	°C	230
Pour point	°C	-39
Total base number	mgKOH/g	7.6
Sulphated ash content	%	0.67

Packaging

